

MOBILE TANKS FOR ADBLUE FDE 2800 - 5000 - 7000



dripless quick-coupling



view of the machine room



automatic delivery nozzle

ELKOPLAST CZ, s.r.o.

Štefánikova 2664, 760 01 Zlín
Czech Republic
tel.: +420 575 571 000
fax: +420 575 571 099
e-mail: elkoplast@elkoplast.cz
www.elkoplast.eu



ADBLUE DISPENSING UNDER CONTROL

Our AdBlue tanks are a response to the increasing need for safe storage of this chemical substance at the users with their own rolling stock, such as farmers, transport companies, firms with their own goods delivery, etc.

The FDE series tanks are double-skinned. The outer shell works as an emergency tank (collector), and is able to contain 110 % of the inner tank volume. The tanks are not fixed to the ground; therefore, there is no building permission necessary for them. They are manufactured from UV-resistant polyethylene, which ensures their long service life and corrosion resistance. Thanks to the seamless production technology, there is no risk of weld cracking and leakage. All of the tanks conform to all standards concerning AdBlue storage. They are equipped with a lockable machine room comprising an integrated dispensing device for simple operation, including an automatic delivery nozzle providing overfill protection.

Advantages and specifications

- Corrosion and UV-resistant, no need to provide it with any coating.
- The inner tank is made of one piece containing no joints.
- The dispensing device is safely located in the lockable machine room.
- 10-year guarantee for the plastic tank, 1-year guarantee for the components.
- The pump with a nominal capacity of 35 l/min.
- Digital flow meter.
- Filling hole D112 with a lid.
- 4 m dispensing hose.
- Automatic delivery nozzle.
- Suction pipe with a filter and a check valve.
- Inner tank ventilation.
- 540 mm manhole on the inner tank.

Options:

- Filling with a dripless quick-coupling.
- Cooling system with a thermostat.
- Heating system with a thermostat.
- Possibility of a monitored access of more users (the Mc Box, Access systems).
- Pneumatic level indicator AFRISO,
- Overflow alarm.

Type	FDE 2800	FDE 5000	FDE 7000
Volume (l)	2800	5000	7000
Length (mm)	2360	2435	2950
Width (mm)	1320	2435	2435
Height (mm)	1880	2300	2300

for more info see www.elkoplast.eu